

PAVEMENT DETAILS FOR ACCESS LANE


NOTES:

1. AN ACCESS LANE IS A SIDE OR REAR LANE PRINCIPALLY PROVIDING ACCESS TO PARKING FOR LOTS WITH ANOTHER STREET FRONTAGE. MAXIMUM VOLUME OF 300 VEHICLES PER DAY. (RESCODE)
2. FOR CONTRACTION AND EXPANSION JOINT DETAILS REFER DRAWING SD306. CONTRACTION JOINTS SHALL BE LOCATED AT 7.0m INTERVALS. EXPANSION JOINTS SHALL BE PROVIDED AT EVERY 4th CONTRACTION JOINT.
3. CONCRETE SHALL BE 25 MPa AT 28 DAYS.
4. CONCRETE SURFACE SHALL HAVE A BROOM FINISH.
5. FOR PARKING BAY DETAILS REFER TO DRAWING SD307.

2 No. 50mm DIA. U.P.V.C. CLASS 12 CONDUITS PER BLOCK, EXTENDED 1500 PAST EDGE OF PAVEMENT, 100 MINIMUM BELOW CARRIAGEWAY SUBGRADE LEVEL.
 FOR FUTURE WATER AND GAS CONNECTIONS. "W" AND "G" TO BE ENGRAVED ON EDGE OF LANE SURFACE ABOVE EACH CONDUIT.

Amendments			
No.	Zone	Detail	Date
1.		Mesh Code Changed	July 06.

INITIALS	DATE	DRAWN :	K. GRAHAM
R.C.	July 06.	CHECKED :	P. TUTTLE
		APPROVED :	S. PLATER
		SCALE :	N.T.S.
		ISSUE DATE:	JUNE 2004

 <p>HUME CITY COUNCIL</p> <p>P.O. Box 119 Broadmeadows Victoria 3047 Telephone (03) 9205 2200 Facsimile (03) 9309 0109</p>	<p>TYPE : ROAD CHARACTERISTIC & PAVEMENT COMPOSITION - ACCESS LANE</p> <p>DRAWING NO: SD 02</p>
--	---