



50mm COMPACTED CLASS 3 FCR BEDDING

SECTION B-B

NOTES:

1. ALL WALLS TO BE 150mm THICK FOR PRECAST CONCRETE COVER DETAILS, REFER TO STD. DWG. SD275
2. CLASS D, CAST IRON COVER AND SURROUND TO BE USED WHEN PIT IS LOCATED IN ROAD PAVEMENT OR WITHIN 1m OF VEHICLE CROSSINGS.
3. PIT TO BE HAUNCHED FOR PIPE DIAMETER OVER 450mm OR DEPTH EXCEEDING 2.0m, REFER TO STD.DWG. SD245.
4. PROVIDE STEP IRONS FOR PIT DEPTH EXCEEDING 1.0m, REFER TO STD. DWG. SD280.
5. CONCRETE STRENGTH 25Mpa AT 28 DAYS

Amendments

No.	Detail	Initials	Date
A			

DRAWN : D. SALAZAR

CHECKED : R. CHARTERS

APPROVED : S. PLATER

SCALE : 1 : 20

ISSUE DATE: JUNE 2004



PO Box 119
1079 Pascoe Vale Road
Brooklands
Victoria 3047
Telephone
(03) 9205 2200
Facsimile
(03) 9309 0109

TYPE :

'V' NOTCH PIT

DRAWING NO:

SD240