



**TYPICAL RESIDENTIAL FOOTPATH CROSS SECTION**

**RESIDENTIAL FOOTPATH JOINT DETAILS**

- NOTES:
1. CONCRETE SHALL BE 25 MPa AT 28 DAYS. (32 MPa FOR INDUSTRIAL, COMMERCIAL, COUNCIL RESERVE & PUBLIC OPEN SPACE).
  2. FORMWORK TIMBER TO BE MIN. 90MM DEEP.
  3. WEAKENED PLANE JOINTS SHALL BE LOCATED AT 1.5m SPACING AND MAY BE MADE WITH A 1" IRON (OR CONCRETE SAW WITHIN 24hrs OF POUR)
  4. THE BARS TO BE INSTALLED AT 300mm MAXIMUM CENTRES COMMENCING 150mm FROM EDGE AT EACH EXPANSION OR CONSTRUCTION JOINTS.
  5. EXPANSION JOINTS AT MAXIMUM 18.0m CENTRES.
  6. THE FINISHED SURFACE SHALL HAVE A LIGHT BROOM FINISH.
  7. FOR JOINT DETAILS REFER TO STD DWG SD306.
  8. ALL DIMENSIONS IN MILLIMETRES UNLESS STATED OTHERWISE.

Amendments		
No.	Detail	Date

DRAWN : C. NGUYEN  
 CHECKED : R. DEVAPURA  
 APPROVED : R. DEVAPURA  
 SCALE : NOT TO SCALE  
 ISSUE DATE: MAY 2012



Po Box 119  
 1079 Pascoe Vale Road  
 Broadmeadows  
 Victoria 3047  
 Telephone  
 (03) 9205 2200  
 Facsimile  
 (03) 9205 2212

TYPE : CONCRETE FOOTPATH DETAILS  
 DRAWING NO: SD303