

Pavement Composition - Rural Road

Pavement Layer	Pavement Material	Pavement Thickness (mm) **							
		Non Expansive Subgrade			Expansive Subgrade				
		CBR 2%	CBR 3%	CBR 4%	CBR 5%	CBR 2%	CBR 3%	CBR 4%	CBR 5%
Surfacing	Size 10 ITP&S								
Base	20mm Class 2 Crushed Rock	100	100	100	100	100	100	100	100
Upper Subbase	20mm Class 3 Crushed Rock	100	100	100	100	100	100	100	100
Lower Subbase	20 or 40mm Class 4 Crushed	250	150	100	60	250	200	200	200
	Rock or Approved Equivalent								
Total		450	350	300	260	450	400	400	400

MINIMUM PAVEMENT THICKNESS:

Non-expansive subgrades 260mm Expansive subgrades

400mm

** EXPANSIVE SOILS ARE CLASSIFIED AS FOLLOWS:

Liquid Limit >70% Plasticity Index >45 Pl x % < 0.425mm >2200 Potential Swell >2.5

				DRAWN: K. GRAHAM	
No.	Zone	Detail	Initials	Date	CHECKED : P. TUTTLE
					CHECKED : P. TUTTLE
					APPROVED : S. PLATER
					SCALE: NTS
					ISSUE DATE: JUNE 2004



PO Box 119 1079 Pascoe Vale Road **Broadmeadows** Victoria 3047

Telephone 03) 9205 2200

Facsimile 03) 9309 0109

<u></u>	$\overline{}$	_	

ROAD CHARACTERISTICS AND PAVEMENT COMPOSITION - RESIDENTIAL RURAL ROAD

DRAWING NO:

SD 08